



# ACP-2300

*Combined panel joining/tape  
attaching machine*





1.



2.



3.



watch the video

1. Pegasus 4- or  
5-thread EXT  
series

2. Double zippy  
edge guide

3. Fabric clamp

- Equipped with Pegasus high-speed 2-needle, 4- or 5-needle safety stitch machine with variable top- or bottom-driven roller featuring a minimum lubrication system to prevent oil stains at the needle bar.
- Combined top- and bottom driven roller, in combination with synchronised puller, guarantees a smooth and fast accurate pattern matching panel joining and the application of Buckram tape.
- Advanced, pneumatic-controlled countour guides with independently adjustable top- and bottom guides (max. 50 mm) for problem-free pattern-matching

and/or joining of panels with uneven selvedge.

- Sewing unit is electrically removable to ease threading, cleaning and maintenance.
- Start/stop drawstrings placed over the full length of the frame provide an important contribution to the efficiency of the machine and the ergonomics for the operator.
- Compact, space-saving frame, equipped with a synchronised conveyor belt with a length of 550 cm.
- Simple and user-friendly operation.

- Production capacity: 50 - 60 panels per hour (average panel length 250 cm)\*.

- Technical specifications:
  - Dimensions: 550 x 160 cm
  - Electric: 220 V, 1 phase, 1350 W
  - Air: 6 bar, 0.5 L per cycle

\* capacity strongly dependent on the operator.