



AGA-2300ST

Fully automatic, programmable vertical curtain cutting machine to cut lined curtains to their final drop and process the top edge



1.



2.



3.



watch the video

1. Buckram tape dispenser
- 2.2 Independent lifting beams
3. LCD touch screen

- Machine is standard equipped with two lifting beams: double lifting beam to attach the lining with spring clamps or the lower hem, and a single lifting beam to attach the lining via the lower hem. Both beams can be optionally equipped with electro-pneumatic clamps.
- Electric extendable table with Buckram tape dispenser to finish the top edge of the curtain.
- Simple operation via the free-standing console with multi-lingual LCD touch screen.
- Adjustable cutting speed and extra tension function for optimal cutting result.
- Machine height made to order, for optimal use of the work space height.
- Available in two widths: 4-panel and 5-panel.
- May also be used in AGA mode, in which only one beam is active and the table function is deactivated.
- Optional foot pedal to move both lifting beams in order to finish the edge seams.
- Production capacity: 30 - 40 panels per hour*.
- Technical specifications:
 - Dimensions: 665 cm or 805 cm wide, height made to order.
 - Electric: 220 V, 1 phase, 1350 W
 - Air: 5 bar, 3 L per cycle

* capacity strongly dependent on the operator.