



# ABS-2400

*Automatic Roman blinds pocket  
tape stitching machine*





1.



2.



3.



watch the video

1. Durkopp Adler with optional tape feeder
2. Adjustable tensioning
3. Mounting beam with pneumatic clamps

- Equipped with Durkopp Adler single or double-needle post bed sewing machine, with reversible top driven roller for faultless stitching.
- Effective sewing width of 450 cm to facilitate stitching of extra-wide Roman Blinds or several blinds simultaneously. The standard height of the machine is 420 cm; can be raised to 620 cm.
- Servo-driven band feed with automatic cutter for accurate feed and trimming of tunnel tape.
- Lifting beam equipped with pneumatic clamps for easy fastening of the fabric.
- Self supporting frame construction, allowing free movement of the machine.
- Industrial Windows-based computer with 15" touch screen allowing for easy operation of the machine. The computer is standard equipped with remote service for technical assistance.
- Optional: UV marking unit to simultaneously mark ring positions and lower hem.
- Optional: Barcode interface, for import of .txt files and .xls table reading.
- Thread breakage sensor for detection of broken upper thread.
- Multi language selection for enhanced user experience.
- Production capacity: 10 blinds per hour.
- Technical specifications:
  - Dimensions: 581 x 140 cm
  - Electric: 220 V, 1 phase, 3500 W, 16 A
  - Air: 7 bar, 3 L per cycle