

ACP-2300

Overlock stitch conveyor curtain sewing machine











watch the video

- 1. Pegasus 4- or 5 thread EXT series
- 2. Optional: Double zippy edge guide 3. Fabric clamp
- Equipped with Pegasus highspeed 2-needle, 4 or 5 thread safety stitch machine with variable top and bottom driven roller featuring a minimum lubrication system to prevent oil stains at the needle bar.
- Combined top transport and bottom roller. And featuring a minimum lubrication system to prevent oil stains at the needle bar.
- Advanced pneumatic controlled single zippy guide for problem free pattern matching when joining panels with even selvedges.

- Sewing unit is electrically removable to ease threading, cleaning and maintenance.
- Start/stop drawstrings placed over the full length of the frame provide an important contribution to the efficiency of the machine and the ergonomics for the operator.
- Compact, space-saving frame, equipped with a synchronised conveyor belt with a length of 550 cm.
- Simple and user-friendly operation.
- Optional: Electro hydraulic height adjustment for ergonomic work positions.

- Optional: Advanced pneumatic controlled double zippy independent guides for problem free pattern matching when joining panels with uneven selvedges.
- Production capacity: 60-75 panels per hour (average panel length 250 cm)*.

Technical specifications:

- Dimensions: 550 x 160 cm
- Electric: 220 V, 1 phase, 1350 W, 16 A
- Air: 6 bar, 0,5 L per cycle
- * capacity strongly dependent on the operator.