



CCP-2300

*Lock stitch conveyor curtain
sewing machine*





1.



2.



3.



watch the video

1. One needle
Juki Lockstich
2. Easily
exchangeable
air injected
hemmer
3. Fabric clamp

- Equipped with high-speed Juki 1-needle lockstitch machine with adjustable top/bottom feed.
- Complete with two multi-functional, easily exchangeable air injected hemmers to produce perfect single and double hems up to a maximum width of 120 mm.
- Sewing unit is electrically removable to ease threading, cleaning and maintenance.
- Start/stop drawstrings placed over the full length of the frame provide an important contribution to the efficiency of the machine and the ergonomics for the operator.

- Compact, space-saving frame, equipped with a synchronised conveyor belt with a length of 550 cm.
- Simple and user-friendly operation.
- Optional: Electro hydraulic height adjustment for ergonomic work positions.
- Optional: Extended puller to process hems up to a width of 180mm.
- Optional: Exchangeable fabric guidance system.

- Optional: Tape feed system to sew pleat tapes.
- Production capacity: 50 panels per hour, bottom and side hems (average panel length of 250cm)*.
- Technical specifications:
 - Dimensions: 550 x 165 cm
 - Electric: 220 V, 1 phase, 1350 W, 16 A
 - Air: 6 bar, 3 L per cycle

** capacity strongly dependent on the operator.*