



DCP-2300

*Double needle conveyor curtain
sewing machine*





1.



2.



3.



watch the video

1. Two needles
Brother
lockstitch
2. Custom made
needle distance
up to 68 mm
3. Fabric clamp

- Equipped with Brother high-speed universal double-needle lockstitch machine with needle and puller feed. Needle spacing per customer specifications.
- Complete with tape feed and guide for perfect application of pleat tape and ripple fold/wave tape.
- Equipped with edge guide and folder for simple positioning of tape in relation to the curtain.
- Sewing unit is electronically removable to ease threading, cleaning and maintenance.
- Start/stop drawstrings placed over the full length of the frame provide an important contribution to the efficiency of the machine and the ergonomics for the operator.
- Compact, space-saving frame, equipped with a synchronised conveyor belt with a length of 550 cm.
- Simple and user-friendly operation.
- Optional: Electro hydraulic height adjustment for ergonomic work positions.
- Optional: Automatic ripplefold tape button counter.
- Production capacity: 75 panels per hour (average curtain width 2,5 panels)*.
- Technical specifications:
 - Dimensions: 550 x 165 cm
 - Electric: 220 V, 1 phase, 1350 W, 16 A
 - Air: 6 bar, 3 L per cycle

* capacity strongly dependent on the operator.