



EPS-2200

*Semi-automatic single pleating and
Microflex hook insertion machine*



1.



2.



3.



watch the video

1. PEA unit for Microflex hooks
2. Low-power alignment laser
3. Nexio touch screen

- Machine equipped with Brother X-Y feed lockstitch sewing machine, pre-programmed to sew curtain pleats up to 12,5 cm in height.
- Fully automatic Microflex curtain hook feed system, with hook height selection in 5 mm increments. The feed system is equipped with a 100-hook container.
- Optional: patented pleat calculation program for positioning seams as desired (inside or next to the pleat).
- Special tack program to attach manual folded double or triple pleats.
- Accurate, easily adjustable low-power alignment laser to monitor even pleat distances.
- Production capacity: 250 pleats per hour*.
- Simple selection of the desired sewing program, speed or thread tension via the Nexio touch screen.
- Adjustable pleat guide.
 - Pleat depth 20-140 mm
 - Pleat distance 65-185 mm
 - Maximum pleat thickness 18mm
- Technical specifications:
 - Dimensions: 120 x 70 cm
 - Electric: 220 V, 1 phase, 600 W, 16 A
 - Air: 5 bar; 0,8 L per cycle
- Optional: Pleat calculation module to easily calculate the pleat depths and distances.

** capacity strongly dependent on the operator.*